FTTH 1X16 SC Fiber Distribution Box

SJ-FTTH-SK18-A1 & SJ-FTTH-SK18-B1

*VP: **Michael Bennett**: mbennett@electronic-links.com*
*Enginering: **John Dee**: johndee@electronic-links.com*
*Managing Director: **Francesco Liburdi**: fliburdi@electronic-links.com*

Electronic Links
international inc
www.electronic-links.com

FTTH 1X16 SC Fiber Distribution Box
Model: SJ-FTTH-SK18-A1
Capacity: 16 Cores SC,
Dimension: 290x210x90mm

Fiber Optic Terminal Box Description

Fiber Optic Terminal Box is able to hold up to 16 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in the FTTx network system. It integrates fiber splicing, splitting, distribution, storage, and cable connection in one solid protection box.

Fiber Optic Terminal Box with the pre-terminated cable could be able to hold up to 16 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in the FTTx network system. It integrates fiber splicing, splitting, distribution, storage, and cable connection in one solid protection box. Pre-terminated Fiber Access Terminal helps save installation time and labor cost by plugging the pre-terminated cable assemblies into the matching fiber adapters without terminating fiber optic cable in the field again.

The equipment is used as a termination point for the feeder cable to connect with drop cable in the FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile, it provides solid protection and management for the FTTx network building.

Fiber Optic Terminal Box Features

1. Total enclosed structure.
2. Material: PC+ABS, wet-proof, water-proof, dust-proof, anti-aging, protection level up to IP65.

3. Clamping for feeder cable and drop cable, fiber splicing, fixation, storage, distribution... etc all in one.
4. Cable, pigtails, patch cords are running through their own path without disturbing each other, cassette type SC adaptor installation, easy maintenance.
5. The distribution panel can be flipped up, feeder cable can be placed in a cup-joint way, easy for maintenance and installation.
6. Cabinet can be installed by the way of wall-mounted or poled-mounted, suitable for both indoor and outdoor uses

Contact Us:

🌐 www.electronic-links.com

VP: Michael Bennett
✉ mbennett@electronic-links.com

Managing Director: Francesco Liburdi
✉ fliburdi@electronic-links.com

- ➢ **Product Name: 1X16 SC PLC FTTH Fiber Distribution Box**
- ➢ **Model: SJ-FTTH-SK18-B1**
- ➢ **Dimension: 290x210x90mm**
- ➢ **Capacity: 16 Cores SC, 1X16 PLC Splitter**

FTTH Fiber Distribution Box Description

FTTH Fiber Distribution Box 1X16 PLC Splitter is able to hold up to 16 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in the FTTx network system. It integrates fiber splicing, splitting, distribution, storage, and cable connection in one solid protection box.

FTTH Fiber Distribution Box with the pre-terminated cable could be able to hold up to 16 subscribers. It is used as a termination point for the feeder cable to connect with drop cable in the FTTx network system. It integrates fiber splicing, splitting, distribution, storage, and cable connection in one solid protection box. Pre-terminated Fiber Access Terminal helps save installation time and labor cost by plugging the pre-terminated cable assemblies into the matching fiber adapters without terminating fiber optic cable in the field again.

The equipment is used as a termination point for the feeder cable to connect with drop cable in the FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile, it provides solid protection and management for the FTTx network building.

FTTH Fiber Distribution Box Features

1. Total enclosed structure.
2. Material: PC+ABS, wet-proof, water-proof, dust-proof, anti-aging, protection level up to IP65.

3. Clamping for feeder cable and drop cable, fiber splicing, fixation, storage, distribution... etc all in one.
4. Cable, pigtails, patch cords are running through their own path without disturbing each other, cassette type SC adaptor installation, easy maintenance.
5. The distribution panel can be flipped up, feeder cable can be placed in a cup-joint way, easy for maintenance and installation.
6. Cabinet can be installed by the way of wall-mounted or poled-mounted, suitable for both indoor and outdoor uses.

Contact Us:

⊕www.electronic-links.com

VP: Michael Bennett
✉mbennett@electronic-links.com

Managing Director: Francesco Liburdi
✉fliburdi@electronic-links.com