

8 Cores IP68 FTTH Fat Box

Electronic Links International, Inc.

Interconnecting Components and Systems

SJ-FTTH-SK18-G



- **8 Cores IP68 FTTH Fat Box**
- **Model: SJ-FTTH-SK18-G**
- **Capacity: 8 Cores, 8pcs SC Adapter**
- **PLC Splitter: 1x8 SC Mini Steel Tube Splitter**
- **Dimension: 280x182x82mm**

FTTH Fat Box Description

FTTH Fat Box is used as a termination point for the feeder cable to connect with drop cable in FTTx network system. FTTH Fat Box integrates fiber splicing, splitting, distribution, storage and cable connection in one solid protection box. Pre-terminated Fiber Access Terminal helps save installation time and labor cost by plugging the pre-terminated cable assemblies into the matching fiber adapters without terminating fiber optic cable in the field again.

FTTH Fat Box Features

- 1.Total enclosed structure.
- 2.Material: PP, wet-proof, water-proof, dust-proof, anti-aging, protection level up to IP68.
- 3.Clamping for feeder cable and drop cable, fiber splicing, fixation, storage, distribution...etc all in one.
- 4.Cable, pigtails, and patch cords are running through their own paths without disturbing each other, micro type PLC splitter installation, easy maintenance.
- 5.Distribution panel can be flipped up, feeder cable can be placed by expression port, easy for maintenance and installation.
- 6.Support pole/wall mounting, aerial cable mounting installation, suitable for both indoor and outdoor use.

FTTH Fat Box Application

CATV networks

Optical fiber communication

FTTX

Fiber optic network convergence

Optical fiber access network

Widely used in FTTH access network

Telecommunication networks

Data communications networks

Local area networks

Contact Us:

 www.electronic-links.com

VP: Michael Bennett

 mbennett@electronic-links.com

Managing Director: Francesco Liburdi

 fliburdi@electronic-links.com