

2 Cores Fiber Optic Protection Box

Electronic Links International, Inc.
Interconnecting Components and Systems



- ✓ Model: SJ-OTB-SY-07
- ✓ Capacity: 2 Cores
- ✓ Material: PC Plastic
- ✓ Protection Grade: IP30
- ✓ Dimension: 180X60X20mm

ElectronicLinks
international inc
www.electronic-links.com

VP: Michael Bennett: mbennett@electronic-links.com
Engineering: John Dee: johndee@electronic-links.com
Managing Director: Francesco Liburdi: fliburdi@electronic-links.com

- **2 Cores Fiber Optic Protection Box**
- **Model: SJ-OTB-SY-07**
- **Capacity: 2 Cores**
- **Material: PC Plastic**
- **Dimension: 180X60X20mm**
- **Protection Grade: IP30**

Fiber Optic Socket Description

SJ-OTB-SY-07 is a Fibre Optic Mini Splice box for optical fiber splicing, cable protection. Fiber Optic Socket can be an Indoor wall mount application.

Fiber Optic Socket Features

Small size, reasonable design for cable protection

Material: PC plastic

3 Cable Ports (1 in 2 out) for max. 4mm diameter optical cable entry & exist

Inside 2 fiber slot for max. 2 fibers splicing.

With fixing cable strengthen core parts

Dust-proof and waterproof

Fiber Optic Socket Application

1. FTTH / FTTX system
2. LAN WAN MAN network
3. GPON ODN network
4. Telecommunication

For more details:

 www.electronic-links.com

Contact Us:

VP: Michael Bennett

 mbennett@electronic-links.com

Managing Director: Francesco Liburdi

 fliburdi@electronic-links.com